

Shenzhen Wanliang Co., Ltd

Hight transparent rate, GOB tech what make the led lamps full sealed, what anti -dust, and waterproof.

Make for window Ads and miracle stage effect.



Product Parameter Table

Parameter Name		Product Parameter	
Cabinet Constitution	Pixel Pitch (mm)	Vertical: 3.9, Horizontal:7.8	Vertical: 7.8, Horizontal:7.8
	Led Type	SMD1921 or SMD2020	SMD1921 or SMD2020
	Cabinet Resolution (WxH)	256x64	128x64
	Cabinet Size (mm)	1000(W)x500(H)	1000(W)x500(H)
	Cabinet Area (m ²)	0.5	0.5
	Cabinet Weight (kg)	4.9	4.9
	Pixel Density (dot/m ²)	32768	16384
	Flatness (mm)	≤0.2	≤0.2
	Maintenance	Front Maintenance	Front Maintenance
	Material	Metal Plate	Metal Plate
	Transparent Rate	72%	72%
Optical Parameters	Brightness Correction	Available	Available
	Color Correction	Available	Available
	Brightness (nits)	≥ 5500 or ≥ 800 (Color Temperature 6500K)	≥ 5500 or ≥ 800 (Color Temperature 6500K)
	Color Temperature (K)	2000-10000adjustable	2000-10000adjustable
	Viewing Angle (H/V°)	160°	160°
	Center Point Deviation	<3%	<3%
	Brightness/Color Uniformity	≥97%	≥97%
Electrical Parameters	Max Power Consumption (W/m ²)	380	400
	Average Power Consumption (W/m ²)	150	125
	Voltage Range	AC100-240V, 50/60 (Hz)	AC100-240V, 50/60 (Hz)
	Security Features	GB4943/EN60950	GB4943/EN60950
Processing	Frame Rate (Hz)	50&60	50&60

Office Address: 8H Gangwan Blvd, 1401 Houhai Rd, Nanshan Dist, Shenzhen, China 518064

Manufacture: 5th Bld. Fulongte Tech. Park, Huaxing Rd, Dalang, Shenzhen, China 518109

Tel: +86 (0)755 2669 2768 Fax: +86 (0) 755 2669 2068

E-mail: sales@szwanliang.net Web: www.szwanliang.net

Shenzhen Wanliang Co., Ltd

Performance	Drive Mode	Constant Current Drive, 16scans	Constant Current Drive, 16 scans
	Gray Scale	14bit	14bit
	Refresh Rate (Hz)	≥1920	≥1920
	Color Figures	16bit	16bit
	Power Failure Function	Save Luminance, Color Correction, Cabinet Parameters	Save Luminance, Color Correction, Cabinet Parameters
Operating Parameters	Life Time (hrs)	50,000 hrs	50,000 hrs
	Operating Temperature /Humidity Range (°C/RH)	-10 - 40/10%-80% (non-condensing)	-10 - 40/10%-80% (non-condensing)
	Storage Temperature /Humidity Range (°C/RH)	-20 - 60/10%-85% (non-condensing)	-20 - 60/10%-85% (non-condensing)
	Certification	CE, ETC and etc.	CE, ETC and etc.

Office Address: 8H Gangwan Blvd, 1401 Houhai Rd, Nanshan Dist, Shenzhen, China 518064

Manufacture: 5th Bld. Fulongte Tech. Park, Huaxing Rd, Dalang, Shenzhen, China 518109

Tel: +86 (0)755 2669 2768 Fax: +86 (0) 755 2669 2068

E-mail: sales@szwanliang.net Web: www.szwanliang.net